

		Model	Fast 40	
		Code Production	917406	
		Interface :		
				
	Overall Dimension (Width-Depth-Height) *open	mm	436x535(870*)x670	
	Packaging Dimension (WxDxH)	mm	610x520x840	
	Gross weight	Kg	34	
	Net weight	Kg	31	
	Volume	mc	0,27	
	Rack size	mm	390x390	
	Max door /hood opening	mm	320	
	Max glasses/plate Height	mm	300/300	
	General construction		single skin	
	Door/hood Construction		double skin	
	Tank construction		welded	
	Tank volume	liter	8	
	Tank heating element	W	600	
	Tank surface strainers		Yes-composite	
	Wash pump type		double flow	
	Wash pump power	W	200	
	Wash temperature	°C	60	
	Boiler type		pressurized	
	Boiler volume	liter	2,6	
	Back-flow system		Valve	
	Boiler heating element	W	2.600	
	Rinse booster pump		NO	
	Rinse booster pump power	W	-	
	Rinse temperature	°C	65	
	Rinse water consumption	Liter /rack	1,6	
	Optimal external water pressure	bar	2 - 4	
	Drain system		overflow	
	Drain filter		double filtering	
	Drain pump		optional	
	Rinse aid dispenser	peristaltic	YES	
	Detergent dispenser	peristaltic	optional	
	Wash cycle	sec	90 - 120	
	Special cycle	programs	-	
	Self cleaning cycle		YES	
	Electric Power	W	3.500	
	Electric Connection	V - ph - Hz	230V 1N 50Hz	
	Fuse	A	16	
	Water softner		NO	
	Plates racks	n°-	NO	
	Flat Rack	n°2	780133	
	Support for saucers	n°-	NO	
	Cutterly Rack	n°1	780139	
	Electric cable	n°1	YES	
	Drain hose	n°1	YES	
	Fill hose	n°1	YES	

