

		Model	Fast 60M	
		Code Production	917290	
		Interface :		
				
				
	Overall Dimension (Width-Depth-Height) *open	mm	575x605(1005*)x820	
	Packaging Dimension (WxDxH)	mm	690x670x980	
	Gross weight	Kg	62	
	Net weight	Kg	56	
	Volume	mc	0,45	
	Rack size	mm	500x500	
	Max door /hood opening	mm	365	
	Max glasses/plate Height	mm	325	
	General construction		single skin	
	Door/hood Construction		double skin	
	Tank construction		welded	
	Tank volume	liter	20	
	Tank heating element	W	2.100	
	Tank surface strainers		Yes-composite	
	Wash pump type		double flow	
	Wash pump power	W	470	
	Wash temperature	°C	60 (55-->65)	
	Boiler type		pressurized	
	Boiler volume	liter	6	
	Back-flow system		valve	
	Boiler heating element	W	3.000	
	Rinse booster pump		no	
	Rinse booster pump power	W	-	
	Rinse temperature	°C	80 (67-->88)	
	Rinse water consumption	Liter /rack	2,1	
	Optimal external water pressure	bar	2 - 4	
	Drain system		overflow	
	Drain filter		double filtering	
	Drain pump		optional	
	Rinse aid dispenser		YES	
	Detergent dispenser		optional	
	Wash cycle	sec	60 - 90 - 180	
	Special cycle	programs	n°1	
	Self cleaning cycle		YES	
	Electric Power	W	3.500	
	Electric Connection	V - ph - Hz	230V 1N 50Hz	
	Fuse	A	16	
	Water softner		NO	
	Plates racks	N°1	780131	
	Flat Rack	N°1	780132	
	Cutterly Rack	N°1	780139	
	Electric cable		YES	
	Drain hose		YES	
	Fill hose		YES	

